

6GT5A

Beam Power Tube

NOVAR TYPE

For Horizontal-Deflection-Amplifier
Service in Black-and-White TV Receivers

Electrical:

Heater Characteristics and Ratings:


| | | |
|--|-----------|-------|
| Voltage (AC or DC) | 6.3 ± 0.6 | volts |
| Current at heater volts = 6.3 | 1.200 | amp |
| Peak heater-cathode voltage: | | |
| Heater negative with respect to cathode. 200 max. volts | | |
| Heater positive with respect to cathode. 200 ^a max. volts | | |

Direct Interelectrode Capacitances (Approx):^b

| | | |
|------------------------------------|------|----|
| Grid No.1 to Plate | 0.26 | pf |
| Input: G1 to (K+G3,G2,H) | 15.0 | pf |
| Output: P to (K+G3,G2,H) | 6.5 | pf |

Mechanical:

| | |
|--|--|
| Operating Position | Any |
| Type of Cathode | Coated Unipotential |
| Maximum Overall Length | 2.880" |
| Seated Length | 2.250" to 2.500" |
| Diameter | 1.438" to 1.562" |
| Dimensional Outline | See General Section |
| Bulb | T12 |
| Base | Large-Button Novar 9-Pin with Exhaust Tip (JEDEC No. E9-88) |
| Basing Designation for BOTTOM VIEW | 9NZ |



Characteristics, Class A₁ Amplifier:

| | Triode Connection ^c | Pentode Connection | |
|---|-----------------------------------|-----------------------|-------|
| Plate Voltage | 150 | 60 250 | volts |
| Grid-No.2 Voltage | 150 | 150 150 | volts |
| Grid-No.1 Voltage | -22.5 | 0 -22.5 | volts |
| Amplification Factor | 4.4 | — | |
| Plate Resistance (Approx.) | — | — 15000 | ohms |
| Transconductance | — | — 7100 | μmhos |
| Plate Current | — | 390 ^d 70 | ma |
| Grid-No.2 Current | — | 32 ^d 2.1 | ma |
| Grid-No.1 Voltage (Approx.) for plate ma = 0.1 | — | — -42 | volts |



RADIO CORPORATION OF AMERICA
Electronic Components and Devices Harrison, N. J.

DATA 1
10-64

6GT5A

HORIZONTAL-DEFLECTION AMPLIFIER

Maximum Ratings, Design-Maximum Values:

For operation in a 525-line, 30-frame system^e

| | | |
|--|-----------|-------|
| DC Plate-Supply Voltage. | 770 max. | volts |
| Peak Positive-Pulse Plate Voltage ^f | 6500 max. | volts |
| Peak Negative-Pulse Plate Voltage. | 1500 max. | volts |
| DC Grid-No.2 (Screen-Grid) Voltage | 220 max. | volts |
| DC Grid-No.1 (Control-Grid) Voltage. | -55 max. | volts |
| Peak Negative-Pulse Grid-No.1 Voltage. | 330 max. | volts |
| Cathode Current: | | |
| Peak | 550 max. | ma |
| Average. | 175 max. | ma |
| Grid-No.2 Input. | 3.5 max. | watts |
| Plate Dissipation ^g | 17.5 max. | watts |
| Bulb Temperature (At hottest point on bulb surface) | 240 max. | °C |

Maximum Circuit Values:

Grid-No.1-Circuit Resistance:

 For grid-resistor-bias operation 1 max. megohm

^a The dc component must not exceed 100 volts.

^b Without external shield.

^c With grid No.2 connected to plate.

^d This value can be measured by a method involving a recurrent wave form such that the maximum ratings of the tube will not be exceeded.

^e As described in "Standards of Good Engineering Practice Concerning Television Broadcast Stations", Federal Communications Commission.


^f This rating is applicable where the duration of the voltage pulse does not exceed 15 per cent of one horizontal scanning cycle. In a 525-line, 30-frame system, 15 per cent of one horizontal scanning cycle is 10 microseconds.

^g An adequate bias resistor or other means is required to protect the tube in the absence of excitation.



6GT5A

AVERAGE CHARACTERISTICS



RADIO CORPORATION OF AMERICA
Electronic Components and Devices
Harrison, N. J.

DATA 2
10-64